



For indoor and outdoor, window graphics, photo paper, backlit films and flat digital print graphics.

Protective Films

## euromedia HighClear Laminate anti-graffiti

The euromedia HighClear Laminate anti-graffiti is a high clear and glossy polyester laminate specially suitable for flat and lie-flat digital prints. The color neutral laminate with UV protection gives the digital print a nice finish and protects at the same time against mechanical influences, graffiti and color fading.

Due to its high transparency, euromedia HighClear Laminate anti-graffiti is especially designed for window graphics. The PVC-free base material is together with the solvent adhesive completely clear and doesn't become milky. Due to its dimensional stability, the material is also suitable for lie-flat graphics such as backlit films or for the finishing of photo applications.

### Dimensions

36mic-1370mm (54'') - 50m

### Product Code

70100118148



### Hints & Tips

If you're looking for a laminate for use in cars or public transport, we recommend our euromedia InSightOut Laminate with certification for motor vehicles according to road traffic licensing regulations (ABG: Allgemeine Bauartgenehmigung nach 22a Straßenverkehrs-Zulassungs-Ordnung ZtVZO; Germany)

## HighClear Laminate anti-graffiti

### Product Properties

#### Applications

- citylights/backlights
- indoor
- outdoor



#### Properties

- PVC-Free

#### Processing Tips

For further processing and when applying, it is recommended to wear gloves, for example euromedia Allrounder Gloves. We recommend that you allow the print to fully dry for minimum 72 hours before finishing. To prevent water penetration and moisture, it is recommended to seal the edges of the print (outdoor use). During lamination and in combination with polyester media, it can lead to a slight electrical voltage.

Not recommended for UV ink. Individual tests might differ in results. Not recommended for (micro) porous surfaces.

In combination with OneWayVision Vinyl please follow the related mounting instructions.

#### Storage

We recommend storing the material in the original case. Store the rolls always together with the label and batch number. Without batch number, no claims can be accepted.

#### Specifications

Material	Polyester
Gloss Level	High glossy
Thickness	36 mic
Liner	36 mic
Adhesive type	Polyacrylate, solvent-based
Adhesive strength	20min:>10; 24h:>12 (FTM1; on glass) (N/25 mm)
Temperature resistency	-30°C to 100°C
Application temperature	5°C to 40°C
Outdoor durability	Up to 2 years (Indoor durability up to 5 years)
Others	Shear strength on glass: 500 hours (FTM8; 1kg, 25mm x 25mm)
Shelf life	2 years

#### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

**euromedia**

#### FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH  
 Heesenstraße 31 40549 Düsseldorf DE  
 Tel: +49 211-5089-326  
 Fax: +49 211-5089-287  
 grafische\_systeme@fujifilm.de