

Technical Data Sheet



ATP Mount

Product: GM- 107 CC

Product Description:

Premium Mounting Tape with excellent clarity and transparency.
For the permanent, self-adhesive lamination of even surfaces. Very well processible, provides excellent adhesion to almost all materials like plastics, films, wood, glasses or metals with excellent flatness. Suitable for in- and outdoor application. Especially suitable for mounting of photographic papers.application.

Product structure:

Support	PET film, 12 µm, transparent
Interliner	on both sides PET-film, 30µm, transparent
Adhesive	pure polyacrylic , permanent, transparent, pH neutral, Solvent free
Total Thickness	0,07 mm
Adhesive weight	60 g/m ²

Characteristics:

	Average Value	Test Method
Adhesion on steel: (after 20 min.)	8 N / 25mm	AFERA 5001
Adhesion on steel: (after 24 h)	11 N / 25mm	AFERA 5001

ATP adhesive systems AG
Sales International, R&D
Sihleggstr. 23, Postfach 127
CH - 8832 Wollerau
Telefon: +41(0)43/888-1515
Telefax: +41(0)43/888-1510
Email: info@atp-ag.ch

More Information can be found on:
www.atp-ag.com

10.08.2017

ATP adhesive systems GmbH
Vertrieb Deutschland
Eichenhofer Weg 71
D - 42279 Wuppertal
Telefon: +49(0)2339/909-750
Telefax: +49(0)2339/909-506
Email: info@atp-ag.com

Application temperature:	min. 10°C
End-Use Temperature range:	from -40°C to +150°C
Shelf life:	2 years (see application information)
Durability:	1 year

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way.

All our products are subjected to a strict quality control by our QM-System. The information is based on our present knowledge and our experience. Because of the large number of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.