

## **JT 8200 WM-PT/PG**

### PRODUCT DESCRIPTION

Budget monomeric calendered self adhesive printing media.

**Face Material:** 90 µm white matt PVC **Adhesive:** 

JT 8200 WM-PT: Solvent acrylic Permanent transparent

JT 8200 WM-PG: Solvent acrylic Permanent grey

Liner: PE Coated Kraft paper, 140 g/m<sup>2</sup>

#### **TYPICAL USE**

Short -term indoor and outdoor promotional graphics on flat smooth surfaces.

### **PROCESSING**

Especially designed for solvent based, eco-solvent, mild solvent, Latex and UV inkjet printing on wideformat printing equipment. To achieve the best possible print quality, please make sure that the correct printer settings are used.

To ensure application suitability, always test the proposed construction under actual application and end-use conditions before going into full production.

### **SHELF LIFE**

1 year when stored at 15 to  $25^{\circ}$ C and  $\pm$  50 % relative humidity (in the original packaging).

# PHYSICAL PROPERTIES (TYPICAL VALUES) Average Values Test Method

Thickness				
Face (micron)	90			ISO 534
Adhesive data, 23	°C (N/	25 r	nm)	
Peel adhesion 180°	on sta	ainle	ess steel	
- 20 min. residence				
JT 8200 WM-PT		12		FTM1
JT 8200 WM-PG		10		
- 24 hour residence				
JT 8200 WM-PT		16		FTM1
JT 8200 WM-PG		15		
Dimensional stab	ility			
Shrinkage (48 hours at 70°C applied on Aluminium)	Max. 1.2 mm		nm	FTM14
Temperature rang	jes			
Minimum application temperature (°C)			+10°C	
Service temperature range (°C)		ge	-20°C to + 70°C	
Flammability				
Fire Classification	B-s1,	40		EN13501-1

# **EXPECTED DURABILITY**Central Europe Zone 1

Unprocessed (vertical exposure) 1 years	ear ISO 4892-2
---	----------------

Note: Exposure to severe temperatures, ultraviolet light, and/or conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitudes and south-facing exposure.



#### DISCLAIMER

For more information on the durability and exposure please visit the "Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Selfadhesive films" on the www.https://www.mactacgraphics.eu website.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see

http://terms.europe.averydennison.com. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

